SAUTER Declaration on materials and the environment

Product



Type TRT317F210 / TRT317F212
TRT327F210 / TRT327F212
Designation Electronic room thermostat for

heating and cooling

Product range Stand-alone controllers

Product group of eco-balance Controllers and sensors

Manufacturer Fr. Sauter AG Im Surinam 55, CH-4016 Basel **Since** Management system certified Ву according to ISO 9001 10 Aug. 1993 SQS ISO 9001:2000 10 Aug. 2002 SQS ISO 14001:2004 10 Aug. 2005 SQS OHSAS 18001:1999 SQS 10 Aug. 2005 **Environmentally-compatible** Management system Basis product design Fr. Sauter AG **Process Business process** Product innovation **Ecological accounting**

Product description	CE conformity		
	Function, operation, maintenance, service	PDS 45.025	
Environmental risk	Fire protection according to	EN 60695-2-11, EN 60695-10-2	
	Fire load ¹ Hazardous substances ² Banned substances (see link below)	2.6 MJ Conforming to RoHS 2011/65/EU Conforming to REACH 1907/2006/EC	
	Parts containing halogen (causing corrosive smoke)	Printed circuit boards	
	Liquids polluting the aquatic environment	None	
	Explosive substances	None	
Packaging ³	Folded cardboard	26 g	

Materials

	Total weight of product 4	8292 g	Material Safety Data Sheet (MSDS)	EU waste code ⁵
Plastic				
ABS		63.8 g	Yes	20 01 39
Metal				
None				
Printed circuit boa	ard			
PCB assembly, lead	d-free solder			
TRT317F210		26.5 g	Not required	20 01 36
TRT317F212		18.2 g	Not required	20 01 36
TRT327F210		28.2 g	Not required	20 01 36
TRT327F212		21.2 g	Not required	20 01 36
Various				
None				

Special components

None

¹ See **Remarks** on last page

² Only applies to electrical devices
³ Directive 94/62/EC and follow-on document, ruling 97/129/EC

⁴ See **Remarks** on last page


⁵ Directive 75/442/EEC and follow-on document, ruling 2001/118/EC



Note

The following materials balance and the calculation of the environmental impact relate to type TRT317F210.

Materials balance



Energy requirement in the utilisation phase

Power requirement for component


Power consumption <0.3 W Typical energy consumption per year 2.6 kWh/a

The energy requirement evaluation was performed for a typical utilisation scenario. The European electricity mix from ecoinvent 2.2 was used to evaluate the power consumption in the utilisation phase.

Calculation of the environmental impact

Evaluation over the entire life stage of 8 years in a typical utilisation scenario. The results additionally shown are based on a method of ecological scarcity that combines various environmental effects into an "environmental impact points" key figure. The method is based on Switzerland's environmental targets and evaluates the individual effects depending on the "Distance to Target".

Indicator	Unit	Production	Utilisation	Disposal	Total
Global warming potential (GWP),					
IPCC 2007, 100a	kg CO2 eq.	2.4	11.3	0.0	13.7
Cumulative energy demand (non-renewable resources)	MJ eq.	47	230	0.1	280
Cumulative energy demand (renewable resources)	MJ eq.	4.3	17	0.00	22
Acidification potential, CML 2001	kg SO2 eg.	5.08E-02	4.65E-02	2.47E-05	9.72E-02
Eutrophication potential, CML 2001	kg PO4 eq.	2.50E-02			
Ozone creation potential, CML 2001	kg C2H4 eq.	2.16E-03	1.87E-03	9.39E-07	4.03E-03
Ecological scarcity 2006 : Total	UBP	7'300	11'500	60	19'000



The relationship of the contributions made by the utilisation in comparison to those made by the production and disposal depends on the intensity of the utilisation (utilisation scenario).

Disposal	Product: The device must be disposed of as waste from electrical and electronic equipment (electrical/electronic scrap) and must not be disposed of as household waste. This applies in particular to the PCB assembly. It is possible that special treatment for special components is compulsory by law or makes ecological sense. Packaging: Recyclable The local and currently valid laws (WEEE2012/19/EU) must be observed.			
	Special information:			
	None			
Remarks	⁽¹⁾ Depending on the fire load for the	(1) Depending on the fire load for the type:		
	TRT317F210, TRT317F212, TRT327F210, TRT327F212	2.6 MJ		
	(2) Depending on the weight of the type:			
	TRT317F210	90 g		
	TRT317F212	82 g		
	TRT327F210	92 g		
	TRT327F212	85 g		
How the environment benefits	ironment benefits With these products we make a significant contribution to energy buildings and to reducing global warming.			
		lucts ensure that customer requirements is cost efficiency over the entire building		
Extent of applicability	This declaration is an environmental declaration based on ISO 14025 a describes the environmental impact of the product over its entire life sta The declaration is made in a compact form without an external check or registration.			
	The data gathered have been evaluated with existing data inventories for production processes from the ecoinvent 2.2 European database.			
	For the determination of the energy requirement during the utilisation phase of the product, standard HVAC applications and average climatic conditions			



Disclaimer: This declaration is only for information purposes.

Deviations from the information it contains can occur without being reported. Fr. Sauter AG explicitly rules out any liability for any consequences that may result due to the above information.

corresponding product group.

in Switzerland were assumed, based on the ecological accounting for the



Your local SAUTER representative will provide further information on environmental aspects, and specifically on disposal.

References

Ecoinvent 2010 ecoinvent data v2.2, Swiss Center for Life Cycle Inventories, Dübendorf FOEN 2008 eco-balances: method of ecological scarcity - eco-factors 2006, FOEN